



**Application Industry:** Oil and Gas Synthetic Resin Non Aqueous Phase System

**Product Name:** Antifoam RK-PP200

RK-PP200 is a 100% active content silicone defoamer which is easy to disperse in solvents.

Under the low adding condition, it shows great defoaming and foam control performance.

**Product property:**

Excellent defoaming ability and foam inhibition

Easy to disperse in solvents

**Main physical and chemical properties:**

Item	Range
Appearance	White to light yellow liquid
Viscosity	1500~6500mPa·s
Active content	100%

**Application Process:**

Directly add into non-aqueous phase system, the suggested addition is 100-1000ppm.

Predisperse in solvent to assist to disperse. The solvent can be kerosene, toluene, etc

Use emulsifier to made be emulsion . The recommended dosage is 5-50% of the total emulsion.

The hydrophobic particles will settle if RK-PP200 is placed for a long time. Please stir it thoroughly before use.

**Key Applications**

Non-aqueous phase system

Petrochemical and gas process

Synthetic resin

**LIMITATIONS**

*This product is neither tested nor represented as suitable for medical or pharmaceutical uses*

**Information of manufacturers and products**

Product name	Antifoam
Model	RK-PP200
Manufacturer	Xiamen Rickman Chemical Technology CO., Ltd. Add: No 1267 Qianpu South Road, Siming District, Xiamen City, Fujian Province, China
Tel/Fax	15359255189

**Product content**

Pure or mixture	Mixture
English name	Silicone

**Dangerous marks**

Human-body health effect	Skin contact	Slightly skin allergic for variety of people
	Eye contact	Eye allergic
	Swallow	No data
Environment effect	No data	
Physical/chemical damage	——	
Special damage	——	

**Packaging & Storage**

Package	50kg plastic pail or 1000kg IBC
Storage Condition	Room Temperature Storage (5℃-40℃) , Avoid direct sun light, shelf life is 12 months.

**LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY**

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of Rickman products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end application.