

Application Industry: Dry Mortar Construction Powder coating

Product Name: Antifoam RK-04P

RK-04P is a kind of high efficiency special powder antifoam . It has excellent defoaming & antifoaming performance. Chemical is stable, not toxic, not corrosive, and not sensitive to acid&alkali.

Product property:

Defoaming and antifoaming quickly

Excellent foam control for a long time

Good storage stability and system stability

Main physical and chemical properties:

Item	Range	
Appearance	Milky white powder or granule	
pH value	4.0~8.0	
Density(g/cm ³)	0.3-0.7	

Application Process:

RK-04P could be added directly. The volume of addition is $0.1\% \sim 0.6\%$. According to your specific condition, optimum volume of addition could be adjusted. Do not dilute.

Key Applications

Cement Mortar

Gypsum, Concrete

Powder coating

Building materials

Oil cementing

LIMITATIONS

This product is neither tested nor represented as suitable for medical or pharmaceutical uses



Information of manufacturers and products

Product name	Antifoam
Model	RK-04P
Manufacturer	Xiamen Rickman Chemical Technology CO., Ltd. Add: No 1267Qianpu South Road, Siming District, Xiamen City, Fujian Province, China
Tel/Fax	15359255189

Product content

Pure or mixture	Mixture
English name	Hydrocarbons and inorganic

Dangerous marks

Human-body health effect	Skin contact	Slightly skin allergic for variety of people
	Eye contact	Eye allergic
	Swallow	No data
Environment effect	No data	
Physical/chemical damage		
Special damage		

Packaging & Storage

Package	15kg/bag	
Storage Condition	Room Temperature Storage (5°C-40°C), Avoid direct sun light, shelf	
	life is 12 months.	

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained here is offered in good faith and is believed to be accurate. However, because conditions and methods of use of Rickman products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end application.